Automatic Inline L'Sealer

ideal for sealing a wide variety of industrial and consumer products

Model:

PP-5600 CS

"APA"



"APA" (Automatic Product Adjustment) machine automatically adjusts inverting head and infeed conveyor to different package sizes from one touch control panel in less than 15 seconds!

Versatile ★ Dependable ★ Affordable

The model PP-5600 CS features "State of the Art" technology, includes Delta PLC with 6" color touch screen control panel, 40 program memory, multiple languages, cycle speeds of up to 40 ppm, a vertical seal head design for greater flexibility and taller packages, "single piece" hot knife seal bar with 2 year warranty, exclusive automatic motorized adjustment of seal head, infeed conveyor and inverting head, variable speed drive 0-95FPM, front load film mount, pin wheel hole punch, self diagnostics on safety sensors, low voltage, broken scrap wind, fast product changeover, self-contained scrap removal system with built-in alarm when full.

Reliability, simplicity and ease of maintenance should provide years of dependable performance at low operational cost. The PP-5600 CS is an extremely versatile machine capable of running a wide variety of industrial or consumer products. The PP-5600 CS features a Motorized Center Seal that allows for precise seam placement and taller package heights.



6" Color Touch-Screen with 40 Presets and Self Diagnostics



"APA" Automatic Product Size Adjustment of Inverting Triangle & Infeed Conveyor *Exclusive Feature!

Automatic Inline L'Sealers



Motorized Adjustment of Seal Head No Crank Handles to Adjust



Optional 3' or 6' flighted or belted infeed conveyor



Available Options:

- Pneumatic Hole Punch
- 3' Flighted Infeed
- 6' Flighted Infeed
- Belted Infeed Conveyors
- Flight Bar Conveyors for Multi-Packs
- Closing Conveyor
- Print Registration



Front Load Film Cradle with Pin Perf Wheels, Saves Space



Vertical Seal Head with One Piece Seal Knife and Blade 2yr Warranty on Seal Blade

Model	PP-5600CS (adjustable center seal)	PP-9070CS
Seal Area	25"L x 20"W x 8"H	35"L x 24"W x 8"H
Machine Speed	Up to 40 PPM	30 to 40 PPM
Electrical	220V, 1 Phase, 20 AMP	220V, 1 Phase, 20 AMP
Air	1CFM @ 80 PSI	1CFM @ 80 PSI
	2.5"W x 3"L	4"W x 5"L
Minimum Pkg Size	24"L x 16"W x 8"H	34"L x 21"W x 8"H
Maximum Pkg Size *	24"	35"
Crated Dimensions	77"L x 62"W x 72"H	105"L x 84"W x 80"H
Shipping Weight	1,500 lbs	2,500 lbs
Warranty	2 years on parts, 2 yrs on seal blade	2 years on parts, 2 yrs on seal blade

^{*}Maximum dimensions may not be combined

■ PP-5600 Dimensions

