



NestaFlex

Gravity 200 RLS Roller Conveyor

* Specifications of models available may vary from the model show

FEATURES

WIDTH: 18", 24" or 30"

width is determined by package size, available conveying area and application specific needs

LENGTH EXTENDED: 8' - 60'

Determine total length needed, including curvatures and obstructions

AXLE CENTER: 5.25", 4" or 3"

center length on fully extended conveyor

ROLLER TYPE

Zinc plated 1 3/8" steel rollers

DESCRIPTION

Designed to expand, contract and move easily, the NestaFlex® Roller is a self tracking, gravity roller conveyor that has a per linear foot capacity of 200 pounds. The all steel construction provides unmatched structural integrity, whether the conveyor is extended, contracted or configured in simple or compound curves.

This unit is engineered to handle odd shaped cartons, drums, and pails in low to medium volume applications. It is the best choice for moving items without a flat, solid surface.





NestaFlex

SPECIFICATIONS

Gravity 200 RLS Roller Conveyor





18" Wide Models		24" Wide Models		I	30" Wide Models		Length Adjustments	
Model #	Leg Sets	Model #	Leg Sets	ı	Model #	Leg Sets	Extended	Contracted
RLS18008S	3	RLS24008S	3	ı	RLS30008S	3	8′ 11″	2′ 5″
RLS18012S	4	RLS24012S	4	ı	RLS30012S	4	12′ 10″	3′ 5″
RLS18016S	5	RLS24016S	5	ı	RLS30016S	5	16′ 9″	4′ 5″
RLS18020S	6	RLS24020S	6	ı	RLS30020S	6	20′ 9″	5′ 6″
RLS18024S	7	RLS24024S	7	ı	RLS30024S	7	24′ 8″	6′ 7″
RLS18028S	8	RLS24028S	8	ı	RLS30028S	8	28′ 5″	7′ 8″
RLS18032S	9	RLS24032S	9	ı	RLS30032S	9	32′ 4″	8′ 9″
RLS18036S	10	RLS24036S	10	ı	RLS30036S	10	36′ 3″	9′ 9″
RLS18040S	11	RLS24040S	11	ı	RLS30040S	11	40′ 2″	10′ 10″

All conveyor products can be modified to suit specific design requirements. Please contact our sales representatives for details on sizes or options that are not listed.

STANDARD FEATURES

Load capacity 200 lbs/ft

Zinc plated 1 3/8" steel rollers

5.25" axle centers

28" – 44" adjustable conveyor heights using hand knobs to raise or lower the legs

Heavy duty steel square tubing zinc plated legs

Welded horizontal leg brace

Heavy duty 5" x 1 ½" casters with 2 total lock brake casters on each end

7 gauge steel side links assembled using shoulder bolts and locking nuts

5/16" diameter axles across the width

Self-tracking

Couplers

Heavy duty retractable package stop

OPTIONS

4" and 3" axle centers
Additional brake casters
Additional set of couplers

Elevations for Adjustable legs

20"-28"

25"-38"

36"-52"

ACCESSORIES

Curve Guards

Technical Data

CONSTRUCTION

All steel bolted construction

LEGS

Zinc plated, heavy duty leg supports
1 1/8", square steel tubing with a welded

SIDE LINKS

Made of 7 gauge stee

WARRANTY

18 month factory warrant

SERVICES AVAILABLE

Technical Support
Application Support