

60" BALER FOR LARGE QUANTITIES OF CARDBOARD

The B6030 is a strong baler for high volumes of cardboard and shrink wrap. Efficient front and rear retainer dogs keep down the waste material.

The low profile construction makes the baler fit standing through an 8 foot dock door, and can be operated under an 11 foot ceiling. Equipped with a GSM system for complete monitoring of the baler and number of bales made.

All Bramidan machines meet ANSI Standards Z245.5 and OSHA Safety Standards; and are equipped with UL® & CUL® Approved Controal Panels.

Ü	\bigcirc
8	-::-







Technical specifications	
Press force (lbs)	66,200
Power supply	208/230/480V 3-phase
Motor (HP)	5.5
Noise level (dB)	62-64
Cycle time (sec)	43
Dimensions WxDxH (inch)	80 x 43 x 129/93
Weight (lbs)	3,700
Feed opening WxH (inch)	60 x 24
Load height (inch)	50
Chamber height (inch)	71
Stroke (inch)	41
Bale size WxDxH (inch)	60 x 30 x 48
Bale weight OCC (lbs)	800-1,200
Bale weight plastic (lbs)	850-1,300









1 Compact your recyclables and eject the bale with a two-handed operation. **2** Move the bales and store until collection. **3** The flexible tying system allow you to use either plastic strapping or metal wire. **4** A full bale light indicates when the baler has reached full capacity.

- Low profile baler B6030 can operate under an 11 foot ceiling
- Easy to operate
 Eject bale system is activated automatically
- High platen pressure
 The 66,200 lbs of pressure ensures heavy bales



Excel Packaging Equipment
Ontario, California - phone 909-923-9292
info@excelpackagingequipment.com