



Touch screen to choose **Function 1: Skin pack**

It keeps the film close to the surface.

Touch screen to choose **Function 2: MAP**

It can extend the freshness of the food by filling in other gas.

Touch screen to choose **Function 3: Vacuum**

Vacuum first, than sealing of trays .

Touch screen to choose **Function 4: Sealing**

Only for heat sealing of trays .

◆ Product usability

Automatic MAP, Vacuum, Skin Pack Sealing and Die Cutting series. It keeps the film close to the surface of the product and is isolated from the air for freshness preservation. 3 additional functions besides Skin Pack, are "MAP, Vacuum and Sealing"

◆ Matching degree

- ✓ Heat sealing
- ✓ Skin pack, MAP, Vacuum, Sealing
- ✓ Replaceable tray
- ✓ Need Air compressor
- ✓ Packed in wooden cases







Y T H S - □ □ □

Tray size

Skin pack

Tray sealer

MODEL	PP-YTHS-390		PP-YTHS-570	
Maximum tray size	1 cavity: 10.6"x15.3"	2 cavity: 10.6"x7"	2 cavity: 15.3"x10.6"	4 cavity: 7"x10.6"
				
Maximum tray height	80mm (3.14")			
Cycle time	20 seconds / 3 cycles per minute			
Voltage	220V - 1 Phase			
Machine dimensions	1080×980×1700 (42"x39x67"H)		1200×1070×1700 (47"x42"x67"H)	
Weight	≈280kg (616 lbs)		≈350kg (770 lbs)	
Max Film diameter	Φ220mm (8.7")			
Air pressure	0.6~0.8Mpa (90 PSI)			
Total power:	≈3.5kw		≈4.0kw	
Vacuum Pump	Shanghai ZhongDe V0040		Shanghai ZhongDe V0063	
Touch Screen	MITSUBISHI 10.3			
PLC	MITSUBISHI FX2N			
Pneumatic accessories	Airtac			
Main Body Material	304 stainless steel			
Mold Material	6061 aluminum			
Electrical Accessories	Schneider			
Thermostat	MH-PT100			