

Fully Automatic Random 4 Edge Taper

Model:

PP-566AEG

Fast, smooth tape sealing for random-sized boxes.



Specifications:

Power Supply	3Ø, 220V, 380V, 415V, 440V
Tape (OPP)	3" (W) x 0.05mm(t) x 1000y(L) x 76Ø(ID)
Capacity	240 Cartons/Hr(60Hz), Regular mode (Machine resets each time) 360 Cartons/Hr(60Hz), Height/Width memory mode
Belt Speed	20M/min. (60Hz)
Min. Sealing Size	300mm L x 250mm W x 150mm H (11.8" L x 9.8" W x 5.9" H)
Max. Sealing Size	700mm L x 500mm W x 500mm H (27.6" L x 19.7" W x 19.7" H)
Table Height	670 - 830 mm (26.4 - 32.7 inches)
Machine Size	1639mm L x 1630mm W x 1658-1818mm H (64.5" L x 64.2" W x 65.3"-71.6" H)
Air	6Kg/cm ²
Net Weight	404Kgs (889 lbs)
Gross Weight	504Kgs (1109 lbs)
Packaging Size	1771mm L x 1762mm W x 1746mm H (69.7" x 69.4" x 68.7")

Features:

- Quick and easy adjustments
- New tape head allows smooth sealing and straight taping
- Four edges sealed and wiped at the same time - fast and smooth
- Width and height automatically adjusted; suitable for random-sized cartons
- Width and height memory function; suitable for uniform cartons
- PLC controlled electric system; can be controlled with infeed/outfeed equipment
- Tape overlap length 60+/-5mm
- 1 Year Limited Warranty

3" Tape

Options:

- With or without infeed power roller conveyor
- With or without outfeed power roller conveyor
- Power-saving 60 second auto-stop
- Safety fence
- 2" or 2.5" tape adapter
- Detection for no tape
- Detection for sealing failure
- Detection for uncut tape